UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/019,705	05/13/2002	Kari Kalliojarvi	915-414	1802
	7590 04/27/200 OLA VAN DER SLUX	Kari Kalliojarvi 915-414 1802  EXAMINER  PEREZ, JULIO R  ART UNIT PAPER NUMI  2617  MAIL DATE DELIVERY M	IINER	
BRADFORD G	REEN, BUILDING 5		PEREZ, JULIO R	
MONROE, CT	REET, P O BOX 224 06468		ART UNIT PAPER NUMBER	PAPER NUMBER
			2617	
			MAIL DATE	DELIVERY MODE
			04/27/2009	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

	Application No.	Applicant(s)				
Office Action Comments	10/019,705	KALLIOJARVI, KARI	KALLIOJARVI, KARI			
Office Action Summary	Examiner	Art Unit				
	JULIO R. PEREZ	2617				
The MAILING DATE of this communic Period for Reply	cation appears on the cover sheet w	ith the correspondence addr	ess			
A SHORTENED STATUTORY PERIOD FOWHICHEVER IS LONGER, FROM THE MADE THE PROPERTY OF THE MADE THE PROPERTY OF THE MADE THE PROPERTY OF THE MADE THE THE MADE TH	AILING DATE OF THIS COMMUN of 37 CFR 1.136(a). In no event, however, may a unication. tutory period will apply and will expire SIX (6) MO will, by statute, cause the application to become A	ICATION. reply be timely filed  NTHS from the mailing date of this community BANDONED (35 U.S.C. § 133).				
Status						
1) Responsive to communication(s) filed	d on <i>09 February 200</i> 9					
	b)⊠ This action is non-final.					
3) Since this application is in condition f	<b>/—</b>	ters prosecution as to the n	nerits is			
closed in accordance with the practic	·	•	101110 10			
Disposition of Claims	<u>-</u>					
	distance of the state of the same is a discount.					
4) Claim(s) <u>1,6,9-11,13-15,19 and 22-3</u>	— · · · · · · · · · · · · · · · · · · ·					
4a) Of the above claim(s) is/ar	e withdrawn from consideration.					
5) Claim(s) is/are allowed.	4.4					
· · · · · · · · · · · · · · · · · · ·	6) Claim(s) <u>1,6,9-11,13-15,19 and 22-31</u> is/are rejected.					
7) Claim(s) is/are objected to.						
8) Claim(s) are subject to restrict	ion and/or election requirement.					
Application Papers						
9)☐ The specification is objected to by the	Examiner.					
10)☐ The drawing(s) filed on is/are: a)☐ accepted or b)☐ objected to by the Examiner.						
Applicant may not request that any objec	tion to the drawing(s) be held in abeya	nce. See 37 CFR 1.85(a).				
Replacement drawing sheet(s) including	the correction is required if the drawing	g(s) is objected to. See 37 CFR	: 1.121(d).			
11)☐ The oath or declaration is objected to	by the Examiner. Note the attache	d Office Action or form PTO	ı <del>-</del> 152.			
Priority under 35 U.S.C. § 119						
2. Certified copies of the priority of	documents have been received. documents have been received in a of the priority documents have been nal Bureau (PCT Rule 17.2(a)).	Application No n received in this National St	tage			
Attachment(s)  1) Notice of References Cited (PTO-892)  2) Notice of Draftsperson's Patent Drawing Review (P <sup>-</sup> 3) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date	ΓΟ-948) Paper No	Summary (PTO-413) (s)/Mail Date Informal Patent Application 				

Application/Control Number: 10/019,705 Page 2

Art Unit: 2617

## **DETAILED ACTION**

1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 02/09/09 has been entered.

## Claim Rejections - 35 USC § 103

- 2. The factual inquiries set forth in *Graham* **v.** *John Deere Co.*, 383 U.S. 1, 148 USPQ 459 (1966), that are applied for establishing a background for determining obviousness under 35 U.S.C. 103(a) are summarized as follows:
  - 1. Determining the scope and contents of the prior art.
  - 2. Ascertaining the differences between the prior art and the claims at issue.
  - 3. Resolving the level of ordinary skill in the pertinent art.
  - 4. Considering objective evidence present in the application indicating obviousness or nonobviousness.
- 3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
  - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 4. Claims 1, 5-8, 10, 11, 13-15,19, 20, 22-31, are rejected under 35 U.S.C. 103(a) as being unpatentable over Wylie et al. (5,974,329) in view of MacDonald (5,732,354).

Application/Control Number: 10/019,705

Art Unit: 2617

Regarding claims 1,15, 23, Wylie discloses a method (and arrangement and a location server) measuring at least one feature of a signal received from the transmitting station at the receiving station, said feature being such that it can be used for determination of the distance between the transmitting station and the receiving station (col. 2, lines 27-28; col. 3, lines 5-7; col. 4, lines 55-62; col. 4, lines 7-10, 39-65, the signal strength from the mobile station may be measured in relation to its position within the different coverage areas; furthermore, the range measurements correspond to power signal measurements); and computing the distance [i.e., range measurement] between the transmitting station and the receiving station using said measured signal feature [i.e., signal strength power] (col. 2, lines 64-67; col. 3, lines 1-16 and 55-65; col. 4, lines 39-67; col. 5, lines 1-4, 66-67-col. 6, lines 1-10, 26-31), determining the current geographical location of one of the transmitting stations (col. 3, lines 3-5); and wherein each base station comprises a plurality of antennas covering a sector of the base station (Figure 3, #'s 12, 13, strongly suggests the use of sector antennas on the base stations or cites).

Page 3

What Wylie does not explicitly disclose is that the method is implemented in the system to store and determine a characteristic parameter describing the line-of-sight conditions of the radio propagation environment of each antenna for two base stations, wherein the characteristic parameter describes excess path lengths caused by obstacles in the environment by means of one of a number of discrete levels; computing distances between the mobile station and the at least two base stations.

MacDonald teaches propagation loss model based on Hata model that includes propagation path slope within different propagation environment schemes, which in turn describe the propagation path, line of sight characteristics, of the terrain, thus, determining factors (levels) for different type of terrain and building density (col. 6, lines 48-67; col. 7, lines 1-59). McDonald further calculating a location estimate of the mobile telephone with receiving a list of signal strengths received by the telephone from cell sites, i.e., base stations within a serving coverage area and hence calculating the distances between the mobile and a plurality of cell sites (Figure 8; col. 6, lines 39-67, -col. 7, lines 1-15).

At the time of the invention, it would have been obvious to one of ordinary skill in the art to modify Wylie to include MacDonald as it is known to implement measurements systems with coefficient factors (levels) or correction factors and determine distances among base stations and the mobile station to provide a more accurate location of the mobile station.

Regarding claim 5, the combination discloses at least one feature comprises at least travel time of the signal between the mobile and base station (Wylie, col. 4, lines 7-10).

Regarding claim 6, the combination discloses at least one feature comprises at least signal travel time differences between the mobile station and base station (Wylie, col. 4, lines 7-10).

Regarding claim 7, the combination discloses at least one feature comprises at least strength of the signal transmitted between the mobile and base station (Wylie, col. 4, lines 7-10, 39-65).

Regarding claim 8, the combination discloses at least one feature comprises the quality of the signal transmitted between the mobile and base station (Wylie, col. 4, lines 7-10, 39-65).

Regarding claims 10, 19, the combination discloses defining propagation environments for several stations; and classifying the stations in different radio propagation environment classes; wherein the characteristic parameter is based on the class of the station (MacDonald, col. 7, lines 30-40).

Regarding claim 11, the combination discloses the characteristic parameter is stored and processed in a location service node implemented in the mobile telecommunications system (MacDonald, col. 7, lines 51-67).

Regarding claim 13, the combination discloses the determination of the characteristic parameter comprises steps of: determining the current geographical location of said mobile station in way that is external to the telecommunications system; and inputting the results of the determination to the telecommunications system (Wylie, col. 3, lines 5-7).

Regarding claim 14, the combination discloses comprising use of a satellite based positioning system said determining of the current geographical location of the mobile station (Wylie, col. 2, lines 64-67; col. 3, lines 1-16; col. 4, lines 39-67; col. 5, lines 1-4, 66-67-col. 6, lines 1-10, 26-31).

Regarding claim 20, the combination discloses wherein the feature of the signal is based on one or several of the following: travel time of the signal between the transmitting and receiving stations, signal travel time difference between the transmitting and receiving stations, the strength of the received signal, the quality of the received signal (Wylie, col. 2, lines 27-28; col. 3, lines 5-7; col. 4, lines 55-62; col. 4, lines 7-10).

Regarding claim 22, the combination discloses the mobile station comprising a sector antenna (Wylie, Figure 1A-1B, and Figure 3, sites with three sector-antennas, #'s 12, 13).

Regarding claim 24, Wylie discloses an arrangement comprising: a first station (col. 4, lines 7-10, 39-65; Figures 1A-1B); a second station for communicating by radio with the first station (col. 4, lines 7-10, 39-65; Figures 1A-1B); means for defining the current geographical location of the first station by means of a source of location information that is external to the telecommunications system (col. 2, lines 64-67; col. 3, lines 1-16; col. 4, lines 39-67; col. 5, lines 1-4, 66-67-col. 6, lines 1-10, 26-31; a GPS system provides location information to mobile and base stations as evidenced by the fact that GPS units, (and within base station transceivers), in a mobile system, are located within mobile stations for providing and facilitating their geographical positions as well as transmitting such positions to respective base stations); determining means for determining a feature of a radio signal received by one of the stations from the other stations (col. 2, lines 64-67; col. 3, lines 1-16; col. 4, lines 39-67; col. 5, lines 1-4, 66-67-

col. 6, lines 1-10, 26-31); each antenna covering a sector of the base station (Figure 3, strongly suggests the use of sector antennas on the base stations or cites).

What Wylie does not specifically disclose is that the method is implemented in the system to store and determine a characteristic parameter describing the line-of-sight conditions of the radio propagation environment of the base station, wherein the characteristic parameter describes excess path lengths caused by obstacles in the environment by means of one of a number of discrete levels; computing distances between the mobile station and the at least two mobile stations.

MacDonald teaches propagation loss model based on Hata model that includes propagation path slope within different propagation environment schemes, which in turn describe the propagation path, line of sight characteristics, of the terrain, thus, determining factors (levels) for different type of terrain and building density (col. 6, lines 48-67; col. 7, lines 1-59). McDonald further calculating a location estimate of the mobile telephone with receiving a list of signal strengths received by the telephone from cell sites, i.e., base stations within a serving coverage area and hence calculating the distances between the mobile and a plurality of cell sites (Figure 8; col. 6, lines 39-67, -col. 7, lines 1-15).

At the time of the invention, it would have been obvious to one of ordinary skill in the art to modify Wylie to include MacDonald as it is known to implement measurements systems with coefficient factors (levels) or correction factors and determine distances among base stations and the mobile station to provide a more accurate location of the mobile station.

Regarding claim 25, the combination discloses comprising means for receiving signals from a satellite based positioning system (Wylie, col. 2, lines 64-67; col. 3, lines 1-16; col. 4, lines 39-67; col. 5, lines 1-4, 66-67-col. 6, lines 1-10, 26-31).

Regarding claim 26, the combination discloses comprising means for determining if an update of the data concerning the radio propagation environment is required (MacDonald, col. 7, lines 5-40).

Regarding claim 27, the combination discloses wherein the first station comprises a portable device (Wylie, col. 2, lines 64-67; col. 3, lines 1-16; col. 4, lines 7-10, 39-67).

Regarding claims 28, 30,, the combination discloses the signal is transmitted from the at least two base stations to the mobile station and the signal is measured at the mobile station (MacDonald, Figure 8, col. 6, lines 39-51).

Regarding claims 29, 31, the combination discloses the signal is transmitted from the at least two base stations to the mobile station and the signal is measured at the at least two base stations (MacDonald, Figure 8, col. 6, lines 39-51, base stations provider means for signal measurements).

5. Claim 9, is rejected under 35 U.S.C. 103(a) as being unpatentable over Wylie in view of MacDonald and Hilsenrath et al., 6,026,304 (hereinafter Hilsenrath).

Regarding claim 9, Wylie in view of Sheynblat and MacDonald does not explicitly disclose, comprising use of a weighted least square method for the determination of distances between the receiving and transmitting stations, wherein the used weighting matrix is the inverse of an error covariance matrix.

Application/Control Number: 10/019,705

Page 9

Art Unit: 2617

However, in a similar field of endeavor, Hilsenrath discloses a method and apparatus in a wireless communication system that accurately determines the transmitter's location (col. 6, lines 6-34-col. 7, lines 9-35-col. 8, lines 15-53).

Therefore, it would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the combination with the teachings of Hilsenrath for the purpose of having an entity that would efficiently and accurately locate the mobile station in a coverage area.

## Response to Arguments

- 6. Applicant's arguments filed on 02/09/09 have been fully considered but they are not persuasive.
- 7. Applicant argues that the combination Wylie and MacDonald relate to single antenna base stations and do not provide any suggestion of how they may be improved to operate with multiple antennas or that Wylie or the combination, at least, fail to disclose or suggest the use of sector antennas, or the use of only two base stations to obtain determination of the location of a mobile station. The examiner disagrees for reasons to follow. Firstly, the claims are written in a very broad fashion and hence, open to a broad interpretation. Wylie strongly suggest the use of two range measurements and information directed to the position angle of the mobile station, which results the position of the mobile can be found, wherein the range measurements are the distance between the base station and the mobile station (col. 2, lines 27-28; col. 3, lines 5-7; col. 4, lines 55-62). Wylie also describes three-sector antenna sites, i.e., Figure 3, #'s 12, 13. Thus, the cited passages read on the limitation.

Application/Control Number: 10/019,705 Page 10

Art Unit: 2617

## Conclusion

8. Any inquiry concerning this communication or earlier communications from the examiner should be directed to JULIO R. PEREZ whose telephone number is (571)272-7846. The examiner can normally be reached on 10:30 - 6:30 PM.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Patrick Edouard can be reached on (571) 272-7603. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/J. R. P./ Examiner, Art Unit 2617

4/19/09 /Patrick N. Edouard/ Supervisory Patent Examiner, Art Unit 2626